

Industrial Water Chiller C3W to C6W

水冷式冷水机

Special Features:

- Powerful quality compressor made in France for high cooling capacity and reliability.
- Employing safe and durable electrical devices and accessories from Europe or Japan.
- High precision temperature control.
- Automatic alarms for breakdowns.
- Compact design for space saving.

特点：

- 进口法国高功能压缩机，提高制冷功能。
- 欧洲、日本进口电器零件，安全耐用。
- 高精度温度控制。
- 自动故障警报。
- 坚固设计，节省空间。



Technical Specification 标准规格

Model 型号		C3W	C4W	C5W	C6W
Cooling capacity 冷冻功能	Kcal/hr	11000	13500	17800	21000
Compressor motor 压缩机马达功率	KW	2.6	3	3.75	4.6
Compressor type 压缩机形式		Hermetic 密封式			
Refrigerant medium 冷冻媒体		R22			
Water pump rating 水泵功能	KW	0.37	0.75	0.75	1.5
Chilled water flow rate 冷水流量	L/min	22.5x4	95	95	260
Pipe inlet/outlet size (D) 出/入水管直径	mm	4x6.3 / 4x6.3	4x6.3 / 4x6.3	4x6.3 / 4x6.3	50/50
Condenser Water Pipe (D) 冷凝器水管直径	mm	20	25	25	40
Dimension HxWxL 高x宽x长	mm	900x570 x785	1060x570 x880	1060x570 x880	1425x680 x1285
Net weight 净重	Kg	120	140	310	340

Specifications, appearances and dimensions are subject to change without prior notice.

CHESO MACHINERY PTE LTD

No.7 Loyang Way, Loyang Industrial Estate
Singapore 508721

Tel: (65) 6545 6566 Fax: (65) 6545 5109

E-mail: sales@cheso.com.sg

CM MACHINERY SDN BHD

No.2A Jalan BP 4/9, Bandar Bukit Puchong
47100 Puchong, Selangor, Malaysia

Tel: (60) 03-80682800 Fax: (60) 03-80681800

E-mail: sales@cmmachinery.com.my

Distributor:

Temperature Controller

自动模温控制机

"CP" Practical Type
"CP"实用型

Special Features:

- Having water tank covered with heat insulating material and microprocessor temperature control, higher temperature accuracy can be attained.
- Water low level protection.
- Tank and heater are made of durable stainless steel for high reliability and safe use.
- European and Japanese electrical spare parts.

特点：

- 不锈钢保温双层水箱设计加强微型电脑数控温度表准确度。
- 缺水警报系统，电子尺控制水高位，自动断电保护。
- 不锈钢发热线，确保安全可靠，耐用。
- 进口欧洲、日本电器零件。



Technical Specification 标准规格

Practical Type Specification

Model 型号		CP4W	CP6W	CP9W
Power rate 电热功率	KW	4.5	6	9
Max. temp 最高温度	deg. C	95	95	95
Medium 传热媒体		Water 水		
Medium capacity 传热媒体容量	L	25 4-15	25 4-15	25 8
Pump power 泵功率	KW	0.5	0.5	0.5
Flow rate 输出流量	L/min	45	45	45
Head 输出扬程	m	75	75	75
Heating method 加热方式		direct 直接		
Cooling method 散热方式		indirect 间接		
Pipe size inlet & outlet 出入水管直径 (D)	mm	4x6.3 / 4x6.3	4x6.3 / 4x6.3	4x6.3 / 4x6.3
Cooling water pipe size 散热水管直径 (D)	mm	20	20	20
Height x Width x Length 高x宽x长	mm	710x300x890	710x300x890	710x300x890
Net weight 净重	Kg	55	58	60
Voltage 电压		380 - 440V 3 Phase/50Hz		

Specifications, appearances and dimensions are subject to change without prior notice.

CHESO MACHINERY PTE LTD
No.7 Loyang Way, Loyang Industrial Estate
Singapore 508721
Tel: (65) 6545 6566 Fax: (65) 6545 5109
E-mail: sales@cheso.com.sg

CM MACHINERY SDN BHD
No.2A Jalan BP 4/9, Bandar Bukit Puchong
47100 Puchong, Selangor, Malaysia
Tel: (60) 03-80682800 Fax: (60) 03-80681800
E-mail: sales@cmmachinery.com.my

Distributor: